



HF ACID PRODUCT OVERVIEW

Performance You Need. Quality You Count On.

For more than 50 years, Honeywell has been the trusted source for HF Acid supply. Our high quality HF Acid is safely and reliably manufactured, transported, and delivered from our state-of-the-art Geismar, La. production facility.

Honeywell

THE #1 CHOICE FOR HF ACID

Our production experience, robust inventory, and industry-leading railcar and truck fleet give us greater flexibility to meet your needs. Our facility in Geismar, LA is the largest HF plant in the world and is operated by Honeywell's highly-trained HF Acid team. We have the HF products you need, when you need them. Why settle for less?

BENEFITS OF USING HONEYWELL HF ACID

- Reliable, U.S.-based production
- Robust supply chain
- Modern rail and truck fleet (Honeywell-employed drivers)
- Technical support
 - Over 1,200 customers and emergency responders trained annually
- Strategically vested – HF Acid is the foundation for Honeywell's next-generation fluorine molecules

APPLICATIONS

Anhydrous HF Acid

- Fluorinated carbon compounds
- Raw materials for petrochemical and plastics industries

Aqueous HF Acid - 70% and 49% Solution

- Stainless steel and titanium pickling
- Glass etching/frosting
- Quartz purification
- Chemical milling
- Feedstock in production of chemical derivatives



	Anhydrous	Aqueous 70% Solution	Aqueous 49% Solution
Appearance	Colorless liquid, fumes in air	Colorless liquid, fumes in air	Colorless liquid
Physical State	Liquid	Liquid	Liquid
Chemical Formula	HF	70% HF in H ₂ O by weight	49% HF in H ₂ O by weight
Specific Gravity	Water=1.0)0.97 @ 70°F (21.1 °C)	Water=1.0)1.225 @ 70°F (21.1 °C)	Water=1.0)1.175 @ 60°F (15.5 °C)
Solubility in Water	100% by weight	100% by weight	100% by weight
Boiling Point	67.2 °F (19.54 °C)	151 °F (66 °C)	224 °F (106 °C)
Melting Point	-118 °F (-84 °C)	-95.8 °F (-71 °C)	-34 °F (-37 °C)
Vapor Pressure	776 mmHg at 70 °F (21.1 °C)	110 mmHg at 70 °F (21.1 °C)	27 mmHg at 70 °F (21.1 °C)
Vapor Density (Air=1.0)	2.21 at 70 °F, 1.76 at 80 °F (26.67°C)	2.21 at 70 °F, 1.76 at 80 °F (26.67°C)	2.21 at 70 °F, 1.76 at 80 °F (26.67°C)
% Volatiles	100%	100%	100%
Ionization Potential	15.98 eV	15.98 eV	15.98 eV
Flash Point	Nonflammable	Nonflammable	Nonflammable



RESPONSIBLE CARE®
OUR COMMITMENT TO SUSTAINABILITY

Although Honeywell International Inc. believes that the information contained herein is accurate and reliable, it is presented without guarantee or responsibility of any kind and does not constitute any representation or warranty of Honeywell International Inc., either expressed or implied. A number of factors may affect the performance of any products used in conjunction with user's materials, such as other raw materials, application, formulation, environmental factors and manufacturing conditions among others, all of which must be taken into account by the user in producing or using the products. The user should not assume that all necessary data for the proper evaluation of these products are contained herein. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liabilities (including, but not limited to, risks relating to results, patent infringement, regulatory compliance and health, safety and environment) related to the use of the products and/or information contained herein.

For more information

To discuss your HF Acid requirements, contact your Honeywell Account Manager or HF Technical Services Manager.

Honeywell HF Acid

115 Tabor Road
Morris Plains, NJ 07950
www.honeywell-hfacid.com

FLR-22-26-EN | 06/22
© 2022 Honeywell International Inc.

**THE
FUTURE
IS
WHAT
WE
MAKE IT**

Honeywell